

TITLE OF THE INVENTION

MOBILE COMMUNICATION TERMINAL DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No. 2000-124493, filed April 25, 2000,
the entire contents of which are incorporated herein
by reference.

BACKGROUND OF THE INVENTION

10 1. Field of the Invention

The present invention relates to a mobile
communication terminal device for use in a mobile
communication system in which, for example, the CDMA
(Code Division Multiple Access) scheme is adopted.

15 2. Description of the Related Art

As a scheme for realizing a next generation
portable telephone system, the W-CDWM (Wideband Code
Division Multiple Access) scheme and the cdma 2000
scheme are standardized and development is conducted
20 on a various types of mobile telephone communication
terminal devices used in this type of system.

For example, there is proposed that a connector
attached with a USB (Universal Serial Bus) terminal is
provided on a mobile terminal device. When the USB
25 interface is used as an external connection interface,
the mobile communication terminal can be simply
connected to a personal computer. Furthermore,

an external device such as a BT (Bluetooth) unit,
a memory card, a keyboard or the like can be simply
connected to the mobile communication terminal.

Then, it becomes possible to appropriately expand
5 a function of the mobile communication terminal by
transmitting control data such as a telephone book or
the like from the personal computer to the terminal of
the mobile telephone to register the data in package
and selectively using various external devices in
10 accordance with the need thereof.

However, in the case where a signal is transmitted
between a plurality of devices by using the USB
interface, it is necessary to provide a USB host
function on at least one of the devices. Such USB host
15 function has a large processing load. Consequently, it
is general that such USB host function is provided on
a device having a high processing capability such as
a personal computer or the like while a USB slave
function is provided on peripherals such as a keyboard,
20 a mouse or the like and small size devices such as
a mobile communication terminal. In such structure,
when an attempt is made to connect an external device
such as BT (Bluetooth) unit, a memory card, a keyboard
or the like to the mobile communication terminal,
25 connection using the USB function cannot be realized
because both have only the USB slave function.

In order to settle this problem, the USB host

function may be provided on the mobile communication terminal. However, in such a structure, it is necessary to provide a large capacity memory and a CPU having a high processing capability on the mobile communication terminal, so that an increase in the consumption power and an increase in cost of the mobile communication terminal are invited.

On the other hand, it is thought that other universal interface such as a serial interface or the like is provided instead of providing the USB host function on the mobile communication terminal. In such a structure, it becomes unnecessary to provide a large capacity memory and a CPU having a high processing capability on the mobile communication terminal. However, apart from the connector having the USB terminal, it is necessary to provide a connector for a serial data interface, which constitutes a large hindrance in an attempt to decrease the size of the mobile communication terminal.

BRIEF SUMMARY OF THE INVENTION

An object of the present invention is to provide a mobile communication terminal device which allows a connection with an external device without providing a large capacity memory, a CPU having a high processing capability and a plurality of types of connectors, so that the consumption power is small, the cost is cheap and the reduction in size is small.

In order to attain the above object, a mobile communication terminal device according to a first aspect of the present invention comprises:

5 one external connector having a predetermined terminal arrangement structure;

10 a first external interface and a second external interface for sending and receiving a signal in accordance with mutually different protocols via the external connector between the mobile communication terminal device itself and the external connector;

a first determination function for determining a type of a third external interface incorporated in the external device connected to the external connector; and

15 an interface selection function.

20 Then, with this interface selection function, an external interface corresponding to the third external interface incorporated in the external device is selected out of the first and the second interfaces on the basis of the determination result of the first determination function.

25 Consequently, according to the first aspect, a type of the third interface incorporated in the external device is determined every time the external device is connected thereto. On the basis of the determination result, a corresponding interface is selected out of the first and the second interfaces

prepared in advance. Thus, even when the external device has any type of external interface, the device can be connected to the terminal of the mobile communication terminal itself.

5 In order to effectively realize the mobile communication device according to the first aspect of the present invention, still another device is made in the present application.

10 A first structure is such that a part of a group of external connector terminals is shared with the first external interface and the second external interface. With such a structure, it becomes unnecessary to provide a connector for each of the first interface and the second interface, so that the number of the external connector terminals can be
15 decreased. Thus, the size of the mobile communication terminal can be decreased.

20 A second structure is such that when a plurality of types (and/or kinds) of external devices are connected to the external connector in the case where voltages output from the specific terminals are set to mutually different values in the plurality of types of external devices which are assumed to be connected, the voltage values output from the specific terminals are
25 detected via a terminal corresponding to the external connector so that the type of the third external interface incorporated in the external device is

determined on the detection result. With such structure, it is possible to determine the type of the third interface on the basis of the voltage value so that the determination is relatively simple.

5 A third structure is such that when a plurality of types of external devices are connected to the external connector with the first determination means in the case where patterns of identification signals output from the specific terminals thereof are set to mutually
10 different patterns in the plurality of external devices which are assumed to be connected, the identification signal pattern output from the specific terminals is detected via a terminal corresponding to the external connector, so that the type of the third external
15 interface is determined on the basis of the detection result. With such a structure, the type of the external device can be determined even when the output voltage value of the external device is the same.

20 A fourth structure is intended to display the determination result by the first determination function. With such a structure, the terminal user can clearly know which external interface is used at the time of the connection of the external device.

25 On the other hand, the mobile communication terminal device according to a second aspect of the present invention further comprises second determination function and a connection control function in

addition to the constituent elements of the first aspect of the present invention. Then, with the second determination function, authentication procedure is conducted with the external device via the first and the second interfaces selected with the interface selection function to determine the connection form of the external device with the terminal of the mobile communication terminal device itself on the basis of the result of authentication. Then, on the basis of this determination, the connection of the external device with its own terminal is controlled with the connection control function.

Specifically, the type and the specification of the external device are detected through exchange of a signal between the external device and the communication terminal device itself via the first external interface and the second external interface selected with the interface selection function to determine whether or not the external device can be connected to the terminal of the mobile communication terminal device itself on the basis of this detection result.

Consequently, according to the second aspect of the present invention, it is determined whether or not the external device can be connected to the terminal of the mobile communication terminal itself on the basis of, for example, the type and the specification of the external device. Consequently, in the case where the

specifications or the like of the external device
differ even when the external interface of the external
device agrees with the mobile communication terminal
device, the external device can be controlled so as not
5 to be allowed to be connected so that highly reliable
external device connection can be realized at all
times.

In addition, the determination result by the
second determination means may be displayed. With such
10 a structure, the terminal user can confirm the
connection form of the external device to his own
terminal so that the terminal user can recognize that
the external device cannot be connected, for example,
when the external device cannot be actually connected.

15 Additional objects and advantages of the invention
will be set forth in the description which follows, and
in part will be obvious from the description, or may
be learned by practice of the invention. The objects
and advantages of the invention may be realized and
20 obtained by means of the instrumentalities and
combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated
in and constitute a part of the specification,
25 illustrate presently preferred embodiments of the
invention, and together with the general description
given above and the detailed description of the

preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a view showing an essential portion of one embodiment of a mobile communication terminal according to the present invention.

FIG. 2 is a view showing a name and a function of each pin of a system connector provided on the mobile communication terminal shown in FIG. 1.

FIG. 3 is a flowchart showing a connection procedure of the mobile communication terminal shown in FIG. 1 and the external device connected to the mobile communication terminal and a content of the connection procedure.

FIG. 4 is a view showing a connection structure in the case where a personal computer having a USB host function is connected to the mobile communication terminal shown in FIG. 1 as the external device.

FIG. 5 is a view showing a connection structure in the case where a memory card without the USB host function is connected to the mobile communication terminal shown in FIG. 1 as the external device.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, referring to the drawings, one embodiment of the present invention will be explained.

FIG. 1 is a view showing an essential portion of a mobile communication terminal corresponding to W-CDMA scheme which is one embodiment of a mobile

communication terminal device according to the present invention. On the mobile communication terminal according to the embodiment, there are provided a host CPU 1, a USB interface 2, a serial control signal interface 3, a switching circuit 4 and a system connector 5 as constituent elements required for the connection with the external device.

Out of the constituent elements, in the beginning, the system connector 5 is provided for connecting the external device not shown to the terminal of the mobile communication terminal itself. The system connector 5 has a total of eleven terminals (pins) P1 through P10, and PRF. FIG. 2 is a view showing the name and the function of these pins P1 through P1 and PRF.

Out of eleven pints P1 through 10 and PRF, pins P1 through P4 are used for USB connection. Out of the pins, P2 and P3 are USB data transmission pin USBD+ and USBD-, so that data is transmitted in bi-directional manner between the mobile communication terminal and the external device not shown via these pins. Furthermore, P4 is a USB power source input pin, so that the USB power source voltage (4.75 through 5.25V) supplied from the external device is input. Incidentally, P1 is a USB grounding pin.

Besides, out of the eleven pins P1 through P10, PRF, pins P5 and P6 are power source input pins for charging to supply the charging voltage and current

supplied from the charger which is one of the external device to a battery circuit not shown. The pin P7 is a synchronizing clock output pin to output a synchronizing clock (64 kHz) to the external device at the time of synchronizing communication with the external device. Incidentally, the electric condition of this synchronizing clock output pin P7 is CMOS2V±0.2V. When the pin P7 is not used, the pin P7 is set to a high impedance (200 kΩ or more).

Furthermore, pins P8 and P9 are manufacturer's option pin and a reservation pin, respectively. In this embodiment, by using these pins P8 and P9, serial data is transmitted between the mobile communication terminal and the external device. Incidentally, the electric condition of the manufacturer's option pin is defined so that the input voltage is set to be 3.6V or less. When the pin P8 is not used, the pin P8 is set to a high impedance (200 kΩ or more).

The USB interface 2 comprises a USB device controller 21, and a detection circuit 22. The USB device controller 21 has a slave function of the USB interface and transmits data via the USB data transmission pins P2 and P3 between the mobile communication terminal device and the external device such as a personal computer or the like having a USB host function.

The detection circuit 22 incorporates the

interface identification voltage supplied from the external device via the USB power source input pin P4 of the system connector 5 to detect the voltage value. In this embodiment, the value of the interface identification voltage generated by the external device having no USB host function is set in advance to a value different from the USB power source voltage (4.75 through 5.25V) at which the external device having a USB function is generated. The detection circuit 22 detects these voltage values respectively to give the detection result to the host CPU 1.

The serial control signal interface 3 sends and receives the serial control signal at the time of transmitting the signal using the serial data interface between the external device and the mobile communication terminal device. In this embodiment, the serial control signal is transmitted via the USB data transmission pins P2 and P3 of the system connector 5.

The host CPU 1 is attached with a serial data interface 11. This serial data interface 11 sends and receives the serial data at the time of transmitting the signal using the serial data interface between the external device and the mobile communication terminal device. In this embodiment, this serial data is transmitted by using the manufacturer's option pin P8 and the reservation pin P9 of the system connector 5.

By the way, a switching circuit is provided

between the USB interface 2 and the serial control
signal interface 3, and the serial data interface 11
in the host CPU 11 and the system connector 5.

The switching circuit 4 is attached with a first and
a second change-over switch 41 and 42. The first and
the second change-over switch 41 and 42 are associated
with each other in accordance with the change-over
control signal generated from the host CPU 1 to operate
switching operation.

The first change-over switch 41 optionally changes
over and connects the USB device controller 21 and the
serial control signal interface 3 with respect to the
USB data transmission pins P and P3 of the system
connector 5. On the other hand, the second change-over
switch 42 turn on and off the connection of the serial
data interface 11 with respect to the manufacturer's
option pin P8 and the reservation pin P9 of the system
connector 5.

As a new function which is concerned with the
present invention, the host CPU 1 comprises first
determination function 1a, interface selection control
function 1b, second determination function 1c and
connection control function 1d.

Out of the functions, in the beginning, the first
determination function 1a incorporates a detection
value of the interface identification voltage from the
detection circuit 22 of the USB interface 2 when the

external device is connected to the system connector 5.
Then, it is determined whether or not the external
device which is connected has a USB host function on
the basis of the detection value of the interface
5 identification voltage.

The interface selection control function 1b gives
the change-over control signal SWC to the switching
circuit 4 on the basis of the determination result by
the first determination function 1a. Then, in the case
10 where it is determined that the external device has
a USB host function, the USB device controller 21 is
connected to the USB data transmission pins P2 and P3
with the first change-over switch 41. Besides, at the
same time, the connection between the serial data
15 interface 11, the manufacturer's option pin P8 and the
reservation pin P9 is set to the OFF state with the
second change-over switch 42.

On the other hand, in the case where it is
determined that the external device does not have the
20 USB host function, the serial control signal interface
3 is connected to the USB data transmission pins P2 and
P3 with the first change-over switch 41. Furthermore,
at the same time, the connection between the serial
data interface 11, the manufacturer's option P8 and the
25 reservation pin P9 is set to the ON state with the
second change-over switch 42.

The second determination function 1c sends an ID

request command to the external device via the USB
device controller 21 or the serial control signal
interface 3 in the state in which each of the
interfaces 2, 3, 11 and the system connector 5 are
5 selectively connected with the control of the interface
selection control function 1b. Then, when the device
ID and the manufacture ID are sent from the external
device, the type of the external device and the
specification thereof which is different from one
10 manufacturer to another are determined on the basis of
these device ID and the manufacturer ID.

The connection control function 1d determines on
the basis of the determination result of the second
determination means 1c whether or not the external
15 device which is connected is a device which can be
connected to the terminal of the mobile communication
terminal device itself. Then, when the external device
cannot be connected thereto, the connection between the
system connector 5 and the main body of the terminal is
20 electrically separated.

An operation of the mobile communication terminal
which is constituted in the manner described above is
explained by using the flowchart shown in FIG. 3.

Incidentally, here an explanation will be made on
25 a case in which a personal computer PC having a USB
host function is connected to the mobile communication
terminal MS and a case in which a memory card having no

USB host function is connected to the PC respectively.

(1) In the case where the personal computer PC is connected to the mobile communication terminal

Suppose that a personal computer PC is connected
5 to a mobile communication terminal device MC via a USB
cable 7 in the state in which the powers source is
turned on. Then, at step S4a, the personal computer PC
generates the USB power source voltage (4.75 to 5.25V)
with the voltage generator 62. This USB power source
10 voltage is supplied to the mobile communication
terminal MS via the USB cable 7 and the USB power
source pin P4 (VBUS) to be input to the detection
circuit 22 in the USB interface 2. When the detection
circuit 22 detects the input of the power source
15 voltage, an interruption signal is given to the host
CPU 1.

After the host CPU 1 of mobile communication
terminal MS conducts initialization at step 3a, the
host CPU 1 monitors the input of the interruption
20 signal at step 3b. Then, when the interruption signal
is input from the detection circuit 22 in this state,
the host CPU 1 determines that the external device is
connected to the system connector 5, so that the
voltage detection value is input from the detection
25 circuit 22 at step 3c. Then, the CPU 1 determines
whether or not the external device has a USB host
function on the basis of the voltage detection value at

step 3d.

For example, when the voltage detection value is the USB power source voltage (4.75 to 5.25V), it is determined that the external device which is connected is a device which has a USB host function. In contrast, the voltage detection value is a voltage other than the USB power source voltage (4.75 to 5.25V), it is determined that the external device which is connected is a device which does not have a USB host function.

By the way, when the type of the external interface incorporated in the external device is determined, the host CPU 1 conducts the change-over control of the switching circuit 4 at step 3e on the basis of the determination result thereof. For example, now, the personal computer PC having the USB host function is connected as an external device. Consequently, the host CPU 1 changes over the first change-over switch 41 to the side of the USB device controller 21. Furthermore, at the same time, the CPU 1 turns off the second change-over switch 42 to set the serial data interface 11 to the no-connection state with respect to the manufacturer's option pin P8 and the reservation pin P9 of the system connector 5.

Subsequently, the host CPU 1 moves to step 3f to create the ID request command here to send this ID request command to the personal computer PC via the

USB device controller 21. The personal computer PC monitors the arrival of the ID request command at step 4b as shown in FIG. 3. In this state, when the ID request command comes from the mobile communication terminal MS, the device ID indicating the type of the device itself and the manufacturer ID are generated to send the device ID and the manufacturer ID to the mobile communication terminal MS.

The host CPU 1 of the mobile communication terminal MS monitors the arrival of the ID at step 3g after sending the ID request command. When the device ID and the manufacturer ID are received in this state, the external device database not shown is accessed on the basis of the device ID and the manufacturer ID at step 3h to determine the type and the specification of the external device. Then, on the basis of the determination result, at step 3i, the external device determines whether or not the external device can be connected to the mobile communication terminal MS itself. Then, in the case where the external device can be connected thereto, the connection port between the system connector 5 and the main body of the terminal is set to the effective state.

Thus, the mobile communication terminal MS and the personal computer PC are connected via the USB interface, so that data transmission control by the upper protocol is made possible between the two

devices.

(2) When the memory card ES is connected to the mobile communication terminal

Suppose that the memory card ES is connected to
5 the mobile communication terminal MS via the cable 9
corresponding to the system connector as shown in
FIG. 5. Then, at step 4a, the memory card ES generates
a power source voltage (3V) which is set to be
different from the USB power source voltage (4.75 to
10 5.25V) with a voltage generator 82 provided for
generating an interface identification voltage.

The interface identification voltage is supplied
to the mobile communication terminal MS via the cable 9
and the USB power source pin P4 (VBUS) to be input
15 to the detection circuit 22 in the USB interface 2.
When the detection circuit 22 detects the input of the
interface identification voltage, the interruption
signal is given to the host CPU 1.

When the CPU 1 of the mobile communication
20 terminal MS detects the generation of the interruption
at step 3b, it is determined that the external device
is connected to the system connector 5. Then, after
the voltage detection value is detected from the
detection circuit 22, it is determined whether or
25 not the external device has a USB host function at
step 3d on the basis of the voltage detection value.
Now, since the voltage is set to a value (2V) other

than the USB power source voltage (4.75 to 5.25V), the external device which is connected is a device that does not have a USB host function.

Then, when the type of the external interface
5 incorporated in the external device is determined, the host CPU 1 conducts the change-over control of the switching circuit 4 at step 3e on the basis of the determination result thereof. For example, now a memory card ES having no USB host function is connected
10 as the external device. As a consequence, the host CPU 1 is changed over the first change-over switch 41 to the side of the serial control signal interface 3. Furthermore, at the same time, the second change-over switch 42 is turned on to connect the serial data
15 interface 11 to the manufacturer's option pin P8 and the reservation pin P9 of the system connector 5.

Subsequently, the host CPU 1 moves to step 3f to create the ID request command here. Then, this ID request command is sent to the memory card ES via the
20 serial control signal interface 3. The memory card ES monitors the arrival of the ID request command at step 4b as shown in FIG. 3. When the ID request command arrives from the mobile communication terminal device MS in this state, the device ID and the manufacturer
25 ID are created at step 4c, the device ID and the manufacturer ID are sent to the mobile communication terminal MS.

The host CPU 1 of the mobile communication terminal MS monitors the arrival of the ID at step 3g after sending the above ID request command. When the device ID and the manufacturer ID are received in this state, the external device database not shown is accessed on the basis of the device ID and the manufacturer ID at step 3h to determine the type and the specification of the external device. Then, on the determination result, it is determined at step 3i whether or not the external device can be connected to the terminal of the mobile communication terminal MS itself. Then, in the case where it is determined that the external device can be connected thereto, the connection port between the system connector 5 and the main body of the terminal is set to the effective state.

Thus, the mobile communication terminal MS and the memory card ED are connected via the serial control signal interfaces 3 and 81 and the serial data interfaces 11 and 83. Then, the serial data can be transmitted by the upper protocol between the two devices.

In contrast, in the case where it is determined on the basis of the determination result of the type of the external device and the specification thereof that the external device cannot be connected to the communication terminal MS, the connection port between the

system connector 5 and the main body of the terminal is set to the cut-off state. Consequently, in the case where the external device which does not conform to the specification of the mobile communication terminal MS is connected thereto, the connection of the external device is cut off so that an unfavorable influence of the external device to the mobile communication terminal MS is prevented in advance.

As has been described above, in this embodiment, the serial control signal interface 3 and the serial data interface 11 are provided in addition to the USB interface 2 having the USB device controller 21 in the mobile communication terminal MS while a switching circuit 4 is provided for selectively connecting these interfaces to the system connector 5. Then, when the external device is connected to the system connector 5, it is determined whether or not the external device has an external interface having the USB host function on the basis of the interface identification voltage supplied from the external device to change over and control the switching circuit 4 on the basis of the determination result and select an appropriate external interface.

Consequently, the USB interface 2 is selected and data is transmitted using the USB interface in the case where the external device which is connected is a personal computer having the USB host function while

the serial control signal interface 3 and the serial data interface 11 are selected to transmit data using a universal serial interface in the case where the external device is a slave device such as a memory card ES or the like having no USB host function.

That is, even when the mobile communication terminal has no USB host function, data can be transmitted by selectively connecting a plurality of types of external devices having different external interface so that the mobile communication terminal MS can be maintained at a low power consumption and a low cost.

Besides, in this embodiment, the USB interface and the serial interface are selectively connected with respect to one serial connector 5. That is, one serial connector 5 is shared with the USB interface and the serial interface. As a consequence, it is not necessary to newly provide a serial interface connector so that an increase in the size of the mobile communication terminal can be prevented.

Furthermore, in this embodiment, the device type of the external device and the name of the manufacturer thereof, namely, the specification thereof is determined by conducting authentication procedure between the external device which is connected and the mobile communication terminal to determine whether or not the external device can be connected to the

terminal of the mobile communication terminal itself.
Then, it is determined that the external device cannot
be connected thereto, the external device is set to
the non-connection state. Consequently, even when
5 the external device having different specification is
connected, a disadvantage can be prevented in advance
in that the mobile communication terminal causes an
error in operation or trouble in some cases with the
external device.

10 This effect is particularly effective in the case
where a charger is connected thereto as the external
device. That is, when the rated value of the voltage/
current of the connected charger is different from the
standard value of the mobile communication terminal, it
15 sometimes happen that the device is heated or catches
fire which is extremely unfavorable. Then, in this
embodiment, when the charger as the external device is
connected, the device ID and the manufacturer ID of the
charger obtained in the authentication procedure are
20 determined so that the charger can not be connected,
the charging power source input pins P5 and P6 and the
power source circuit in the portable communication
terminal are cut off to prevent the charging thereof.
Consequently, even when a charger having a different
25 standard is connected, heating and fire can be
prevented with certitude.

Incidentally, the present invention is not limited

thereto. For example, the present embodiment has a USB interface having a USB slave function and a universal serial interface to constitute a structure in which the external interface is selected in accordance with the type of the external interface incorporated in the external device which is connected. However, the present invention may not necessarily be limited thereto. The present invention may comprise a plurality of types of external interfaces such as RS232C, SPI, I3BUS, IEEE1394 to select these external interfaces in accordance with the types of the external interface incorporated in the external device.

Furthermore, in the above embodiment, there has been explained a case in which an USB interface having the USB slave function is provided on the mobile communication terminal MS. However, the invention may be constituted in such a manner that a simple host function of USB which is constituted so that processing addition becomes smaller than the USB host function provided on the external device having a high processing capability or the like such as, for example, a personal computer or the like.

With such a structure, it becomes possible to transmit data using the USB interface between the terminal of the mobile communication terminal and a majority of external devices having only USB slave function without increasing a memory capacity of the

mobile communication terminal MS and a processing capability of the CPU.

Furthermore, in the above embodiment, there has been explained a case in which the type of the external interface incorporated in the external device is
5 determined on the basis of the interface identification voltage generated by the external device. However, the invention may be constituted in such a manner that the type of the external interface is determined by
10 supplying one bit or two bits identification signal instead of the interface identification voltage so that the type of the external interface is determined by supplying the identification signal to a specific connector pin of the mobile communication terminal from
15 the external device.

Apart from it, with respect to the structure of the first and the second determination means and the determination content, the structure of the interface selection means, the structure of the connection
20 control means, the type of the external device, the type of the external interface and the like can be modified in various ways without departing from the gist of the invention.

Additional advantages and modifications will
25 readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments

shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000